

QUALITY CERTIFICATE

№ 2025679956 Issued Date: 09.06.2025

Seller: PlasmaTec LLC
 18 Pravednykiv svitu str., Vinnytsia, Vinnytsia
 region, Vinnytsia district, Ukraine, 21036
 Country of MFR: Italy

Customer: Monolith Bison Inc
 501-10022 110 Street Nw,
 Edmonton, Alberta, T6V 0C6, Canada

Product
Welding wire copper coated Monolith ER70S-6 TM MONOLITH d 1.2 mm (.045"): pack 5 kg (11 LB) / Spool

Specification/Classification	AWS A5.18/SFA-5.18: ER70S-6 CSA W48: B-G 49 A 3C 1 S6 (ER49S-6) EN ISO 14341-A – G42 4M 21 3Si1/ G 38 2 C1 3Si1
Lot Number	754529

**Mechanical properties of weld metal
 EN 10204, type 2.2**

Shielding gas according to EN ISO 14175	M21	CO₂
Tensile strength, MPa (N/mm²)	500-640	470-600
Yield strength, MPa (N/mm²)	≥ 420	≥ 380
Elongation, A5%	22	22
Impact energy (KV), J	(-40°C) ≥ 47	(-30°C) ≥ 47

**Chemical analysis, %
 EN 10204, type 3.1**

C	0.064	Cr	0.038
Mn	1.44	Al	0.001
Si	0.853	Ti	0.001
S	0.018	B	0.0004
P	0.010	V	0.002
Cu	0.016	Ca	0.0005
Mo	0.004	Zr	0.0001
Ni	0.026	Pb	0.0010
Ti+Zr	0.0011	Nb	0.0010

Post weld heat treatment - As welded

The product was manufactured and supplied according to a Quality System Program that meets the requirements of ISO 9001.

Head of Technical Control: Andrii Babyn



(signature)
 quality@plasmatec.com.ua, +380(67)433-19-36 (Viber, WhatsApp, Telegram)